

BATTERY MATERIAL/PRODUCT SAFETY DATA SHEET

DC/QR-7N035-07

1. Identification of the Substance or Preparation and Company

Product	Li-ion cells and batteries
Model	Li-ion 5517170 11.1V 1500mAh 16.65Wh

2. Composition&Information on Ingredients

Chemical Composition	CAS No.	EC#	Weight (%)
Lithium Cobalt Oxide	12190-79-3	235-362-0	39.6
Aluminum	7429-90-5	231-072-3	5.56
PVDF Poluvinyldence Fluoride	24937-79-9	200-867-7	1.15
Graphite	7782-42-5	231-955-3	23.2
Copper	7440-50-8	231-159-6	9.8
SBR Styrene-Butandiene Rubber	9003-55-8	—	1.78
PE Poly Ethylene	9002-88-4	200-815-3	0.06
PP Polypropylene	9003-07-0	—	0.78
Lithium Hexafluorophosphate	21324-40-3	244-334-7	15.35
EC Ethylene Carbonate	96-49-1	202-510-0	2.72

3. Hazards Identification

Do not short circuit, puncture, incinerate, crush, immerse, force discharge or expose to temperature above the declared operating temperature range of product. Risk of fire or explosion. Under normal conditions of use, the electrode materials and liquid electrolyte they contain are not exposed to the outside, provided the battery integrity is maintained and seals remain intact.

Effects of Overexposure

Eye Effects: In the case of a fire or cell rupture the electrolyte solution inside battery is extremely corrosive to eye tissue and may result in permanent blindness. Contact with nickel oxide may cause minor irritation.

Skin Effect: Contact with electrolyte solution inside battery may cause serious burns to skin tissues. Contact with nickel compounds may cause result in chronic eczema or nickel itch.

Ingestion: Ingestion of electrolyte solution causes tissue damage to throat area and gastro/respiratory tract. Ingestion of nickel compounds causes nausea and intestinal disorders.

Inhalation: No exposure possible except in the case of fire or abuse. Effects of inhalation of nickel compounds vary from mild irritation of nasal mucous membranes to damage of lung tissues proper.

4. First Aid Measures

The information below refers to exposure to the ingredients.

Battery Electrolyte:

Eye Contact: Flush with plenty of water for at least 15 minutes if abuse causes safety vents to activate. Get immediate medical attention.

Skin Contact: Remove contaminated clothing and flush effected areas with plenty of water for at least 15 minutes. Wash with soap and water.

Ingestion: Do not induce vomiting. Dilute by giving water. If available give several glasses of mild. Get immediate medical attention. Do not give anything by mouth to an unconscious person. Call a physician or Poison Control Centre immediately.

Inhalation: Remove to fresh air. Give oxygen or artificial respiration if needed. Get immediate medical attention.

Further treatment: Show this safety data sheet to the doctor in attendance.

5. Fire Fighting Measures

Suitable extinguishing media

Dry powder, carbon dioxide (CO₂), sand.

Extinguishing media which must not be used for safety reasons

Water, water spray.

Specific hazards

Risk of receptacle bursting.

Special protective equipment for firefighters

In the event of fire, wear self contained breathing apparatus. Wear personal protective equipment.

Hazardous decomposition products

Nickel and cobalt compounds.

6. Accident release measures

The information below refers to exposure to the ingredients.

Personal precautions

Remove personnel from area until fumes dissipate. Use personal protective equipment. Avoid contact with skin and eyes.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

Do not allow material to contaminate ground water system.

Methods for cleaning up

Pick up and transfer to properly labelled containers. Dispose of in accordance with local regulations.

7. Handling and Storage

Handling	<p>The cells and batteries manufactured from them may be highly charged and are capable of high-energy discharge. Care should be taken to handle cells properly to avoid shorting or misuse that will result in rapid uncontrolled electrical, chemical, or heat energy release.</p> <p>Do not short circuit. Do not disport cell. Do not allow an exposed flame or spark to come near the cells. Do not mix new and used batteries. Keep batteries in non conductive trays.</p>
Storage	<p>The cells and batteries shall not be stored in high temperature, the maximum temperature is 60°C (less than one month), otherwise the cells and batteries may be leakage. Besides, the cells and batteries shall be protected from short circuit and protected from movement that could result in short circuit.</p>
Other	<p>Follow manufacturer's recommendations regarding maximum recommended currents and operating temperature range.</p>

8. Exposure Controls & Personal Protection

Exposure Limit Values	<p>Nickel hydroxide, 0.5mg(NI)/m³ TWA</p> <p>Potassium Hydroxide, 2mg/ m³ MAC</p>
Respiratory protection	<p>Use NOISH/MSHA approved respirator if cell broken open during a fire to maintain exposure levels below the TWA for hydrogen absorbed alloy and nickel compounds.</p>
Hand protection	<p>If exposure to electrolyte solution, or dried salts is likely, use any water-insoluble non-performance glove, i.e., synthetic rubber. Do not use leather or wool.</p>
Eye protection	<p>Use splash goggles or face shield if cell activates due to abuse.</p>
Other	<p>Rubber apron or equivalent if exposure to electrolyte solution is likely.</p>

9. Physical and Chemical Properties

Appearance	Sealed battery
Odour	Odourless
Color	N/A
PH	N/A
Flash Point	N/A unless individual components exposed
Flammability	N/A unless individual components exposed
Relative density	N/A unless individual components exposed
Solubility(water)	N/A unless individual components exposed
Solubility(other)	N/A unless individual components exposed

10. Stability and Reliability

Stability	Stable under normal conditions
Condition to avoid	Keep away from heat and sources of ignition
Material to avoid	Aluminum, zinc and other active metals, acid, chlorinated and aromatic hydrocarbons, nitro-carbons, halocarbons. Water.
Hazardous Polymerization	Hazardous Polymerization does not occur
Hazardous decomposition Products	Nickel oxide, and potassium hydroxide

11. Toxicological Information

The information below refers to exposure to the ingredients	
Acute toxicity	Nickel hydroxide LD50/oral/rat = 1500mg/kg potassium hydroxide LD50/oral/rat=273mg/kg
Local effects	Causes severe burns. Risk of serious damage to eyes. Harmful by inhalation and if swallowed.
Long term toxicity	No data available. Avoid repeated exposure.
Specific effects	May cause sensitization by inhalation and skin contact. Limited evidence of a carcinogenic effect.

12. Ecological Information

Mobility	None known if used/disposed of correctly
Persistence and degradability	None known if used/disposed of correctly
Ecotoxicity effects	None known if used/disposed of correctly

13. Disposal Considerations

Waste from residues/unused products	The battery is a hazardous waste under RCRA. Dispose of in accordance with appropriate local regulations. Should not be released into the environment.
Contaminated packaging	Not applicable

14. Transport Information

a) In general, all batteries in all forms of transportation (ground, air, or ocean) must be packed in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packed in a manner that prevents short circuits and be contained in “strong outer packing” that prevents spillage of contents. All original packing for nickel metal hydride batteries has been designed to be compliant with these regulatory concerns.

Nickel metal hydride batteries (sometimes referred to as “Dry cell” batteries) are not defined as dangerous goods under the IATA Dangerous Goods Regulations 57nd edition 2016, ICAO Technical Instructions and the U.S hazardous materials regulations (49 CFR). These batteries are not subject to the dangerous goods regulations as they are compliant with the requirements contained in the following special provisions.

Regulatory Body	Special Provisions
ADR	295-304, 598
IMO	UN 3496 SP117 and SP963
UN	UN 3496
US DOT	49 CFR 172, 102 Provision 130
IATA	A199

In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words “not restricted” and the Special Provision number A199 be provided on the air waybill, when an air waybill is issued.

b) International Maritime Organization (IMO) IMDG Code regulated these products as UN 3496 BATTERIES, METAL HYDRIDE, class 9 dangerous goods with Special Provision 117 and 963 assigned.

SP117

Only regulated when transported by sea.

SP963

Nickel-metal hydride button cells or nickel-metal hydride cells or batteries packed with or contained in equipment are not subject to the provisions of this Code.

All other nickel-metal hydride cells or batteries shall be securely packed and protected from short circuit. They are not subject to other provisions of this Code provided that they are loaded in a cargo transport unit in a total quantity of less than 100 Kg gross mass. When loaded in a cargo transport unit in a total quantity of 100 Kg gross or more, they are not subject to other provisions of this Code except those of 5.4.1, 5.4.3 and column (16) of the dangerous good list in Chapter 3.2.

The requirements of these sections are:

- (1) Dangerous goods transport documentation to accompany the shipment.
- (2) The shipment must be described as “UM3496, BATTERIES, NICKEL-METAL HYDRIDE, CLASS 9” on the shipper’s declaration for dangerous goods.
- (3) The dangerous goods description must also be entered on the Dangerous Cargo Manifest and/or the detailed stowage plan in compliance with the IMDG Code requirements for shipboard documentation.

15. Regulatory Information

The preparation is classified as dangerous in accordance with Directive 1999/45/EC.	
Symbol	C - Corrosive N – Dangerous for the environment
R -phrases	R35 - Causes severe burns. R40- Limited evidence of a carcinogenic effect. R20/22- Harmful by inhalation and if swallowed. R42/43- May cause sensitization by inhalation and skin contact. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S -phrases	S 1/2- Keep locked up and out of the reach of children. S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection. S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S60 - This material and its container must be disposed of as hazardous waste. 561 - Avoid release to the environment. Refer to special instructions/safety data sheets.

16. Other Information

None

Date issued: 2017/04/05

Last Date Revised: 2017/04/05

Note: This information has been compiled from sources considered to be dependable and is accurate and reliable. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his own particular use. We do not accept liability for any loss or damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information nor do we offer warranty against patent infringement.

Approved by: 王重威

Date: 2017-04-05